

FARGO® HDP600ii

Print Method	HDP® Dye-Sublimation / Resin Thermal Transfer
Resolution	600 dpi (23.6 dots/mm)
Colors	Up to 16.7 million / 256 shades per pixel
Print Ribbon*	Full-color with resin black, YMCKIKI*, 600 prints
HDP Film	Clear (1500 prints)
Accepted Standard Card Sizes	CR-80 (3.375"L x 2.125"W / 85.6mmL x 54mmW)
Print Area	Over-the-edge on CR-80 cards
Accepted Card Thickness	030" (30 mil) to .050" (50 mil) / .762mm to 1.27mm
Accepted Card Types	ABS, PVC, PET, PETG, proximity, smart and mag stripe cards, polycarbonate
Input Card Cartridge Capacity	100 cards (.030" / .762mm) and exception card feed slot
Output Hopper Card Capacity	200 cards (.030" / .762mm)
Card Cleaning	Replaceable cleaning roller (included with each print ribbon)
Memory	1 GB RAM
Display	User-friendly, SmartScreen™ Graphical OLED Control Panel
Software Drivers	Driverless printer, SDK development required
Encoding Options	Supported smart card and magnetic stripe technologies: - ISO 14443 A/B, ISO 15693) read/write encoder - Contact smart card encoder reads from and writes to all ISO7816 1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards - ISO magnetic stripe encoding, dual high- and low-coercivity, tracks 1, 2 and 3
Interface	Ethernet (100 Mbps) with internal print server
Operating Temperature	65° to 90° F / 18° to 32° C
Humidity	20 - 80% non-condensing
Dimensions	HDP600ii + Dual-Sided Module: 13.0"H x 19.75"W x 12.0"D / 330mmH x 502mmW x 305mmD
Weight	HDP600ii + Dual-Sided Module: 24.6 lbs. / 11.2 kg
Certifications	UL, FCC
Supply Voltage	100-240 VAC, 2.5A max
Supply Frequency	50 Hz / 60 Hz
Warranty	- Printer - Three years - Printhead - Lifetime; unlimited card passes
FARGO Secure Materials	FARGO Card Printer/Encoders require highly specialized media to function properly. To maximize printed card quality and durability, printhead life and printer/encoder reliability, use only HID Secure Materials. HID warranties are void, where not prohibited by law, when non-HID Secure Materials are used.
Printer Security	Financial card association-compliant electronic and mechanical locks for input hopper, card reject bin and consumables access; Kensington® lock compatible with security cable slot (lock and cable not included); Bolt-down provision to secure printer to work area; Output hopper card concealment; TLS 1.2 encryption (support for Triple DES and AES-256)

* Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, I=Inhibit


hidglobal.com

North America: +1 512 776 9000

Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800

Latin America: +52 55 9171 1108

© 2020 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, FARGO, and HDP are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.
2020-06-29-si-fargo-hdp600ii-printer-spec-en
PLT-05126